

BUILT TO PUSH YOUR PROJECT FORWARD.



SHANTUI DOZERS / NOW ENQUIRE THROUGH CONAGRI

GET THE RIGHT DOZER FOR THE GROUND.

Bulk earthworks. Site clearance. Road formation. Quarry maintenance. Conagri can discuss the machine, blade and track setup for your job.



CIVIL ENGINEERING & LAND WORK



QUARRIES & HEAVY EARTHMOVING

XL OR LGP? / BLADE & RIPPER? / UK SITE REQUIREMENTS?

Tell us what you are pushing and where you are working. We will help match a suitable Shantui specification to your project.

CALL 07841 036064

Conagri Limited | Shantui dozer enquiries

www.conagri.com

CHOOSE YOUR WORKHORSE

DH13M & DH16M | published manufacturer specifications

DH13M

14390 – 16090 kg
115 kW

DH16M

17665 – 20375 kg
149 kW

XL / LGP OPTIONS



SPECIFICATION	DH13M XL	DH13M LGP	DH16M XL	DH16M LGP
Operating weight	14390 kg	14990 kg	17665 kg	18830 kg
Rated power	115 kW	115 kW	149 kW	149 kW
Rated engine speed	2200 rpm	2200 rpm	2200 rpm	2200 rpm
Ground pressure	46.3 kPa	35.6 kPa	50 / 45.9 kPa*	36.9 kPa
Track shoe width	560 mm	760 mm	560 / 610 mm	810 mm
Fuel tank	263 L	263 L	389 L	389 L
Blade digging depth	460 mm	460 mm	642 mm	642 mm
Ripper digging depth	500 mm	500 mm	492 mm	492 mm

XL FOR FIRMER GOING. LGP FOR LOWER GROUND PRESSURE.

Discuss ground conditions, transport width and attachments before specifying.

*DH16 XL pressure depends on 560 / 610 mm track shoes. Figures include drawbar where stated.

Published data: Shantui DH13M and DH16M product pages; configurations may change.

UK emissions compliance, warranty, lead time and final specification require confirmation.

Pictures are illustrative and do not identify the models in the comparison.

Manufacturer sources: shantui.com/product/pro-detail-1304040.htm

shantui.com/product/pro-detail-1304052.htm

CALL 07841 036064

Conagri Limited | Shantui dozer enquiries

www.conagri.com